



TECHNOMELT®

TECHNOMELT SUPRA 90

Benefits

- High-quality synthetic hotmelt adhesive
- Excellent processing quality and adhesion characteristics
- High heat resistance
- Excellent cold flexibility
- Very high hot tack
- Extremely thermostable



TECHNOMELT SUPRA 90

Application Areas

- Versatile product for gluing of wrap-around cases, tray forming and folding boxes
- Bonding paper and carton, including printed and lacquered surfaces
- Permits high machine speeds

MELTER, HOSES, SPRAY HEADS AND NOZZLES

TECHNOMELT PUR CLEANER ME 4KG

For the cleaning of melting tanks and application systems, we recommend the use of our HOTMELT CLEANER TECHNOMELT PUR CLEANER ME. For the cold cleaning of surface soilings on application equipment, conveyor belts or other machine parts, TECHNOMELT CLEANER MELT-O-CLEAN can be applied. During use, please follow the safety instructions.

FOR MORE INFORMATION, PLEASE ASK FOR OUR CLEANING GUIDE.

Features

Color	White
Setting speed	Fast
Viscosity	1,200 to 1,700 mPas @160°C
Optimal processing temperature	150 – 180 °C
Packaging	26 kg sack



GET IN CONTACT WITH US

Henkel Adhesives Technologies India Pvt Ltd
L&T Seawoods, Grand Central,
401, B Wing , 4th Floor, Tower 1,
Seawoods, Navi Mumbai – 400706
Maharashtra, India

www.henkel.com/consumerpackaging

The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to any verbal recommendation, except for cases where we are liable of gross negligence or false intention. The information is protected by copyright. In particular, any reproductions, adaptations, translations, storage and processing in other media, including storage or processing by electronic means, enjoy copyright protection. Any exploitation in whole or in part thereof shall require the prior written consent of Henkel AG & Co. KGaA. Except as otherwise noted, all marks used in this document are trademarks and/or registered trademarks of Henkel and/or its affiliates in the US, Germany, and elsewhere. © Henkel AG & Co. KGaA, 08/2023

Henkel